













## CARATTERISTICHE TECNICHE - TECHNICAL FEATURES

standards	characteristics or properties	declared values
 ISO 10545-3	assorbimento d'acqua water absorption	<0.5%
 ISO 10545-4	resistenza alla flessione (R) breaking strength	35 N/mm <sup>2</sup>
 ISO 10545-13	resistenza agli acidi resistance to acid	GLA
 ISO 10545-12	resistenza al gelo frost resistance	resiste frost proof
 ISO 10545-14	resistenza alle macchie stain resistance	4
 ISO 10545-2	planarità surface flatness	±0.5%
	spessore thickness	10 mm
 DIN 51097 DIN 51130 DCOF BOT3000	coefficiente d'attrito (scivolosità) static coefficient of friction	A+B R10 >0.42
	variazioni cromatiche color shade	V2 variazione leggera V2 slight variation


## TECHNICAL INFORMATION & PLUS

### FORMATI - SIZES



RETTIFICATO

80 x 80  
32" x 32" 65




RETTIFICATO

60 x 60  
24" x 24" 54



RETTIFICATO

30 x 60  
12" x 24" 51



MOSAICO

30 x 30  
12" x 12" 140



HEXAGON

30 x 34  
12" x 13" 34


### DECOR PROJECT



BATTISCOPA SMALTATO  
RETTIFICATO

7 x 60  
3" x 24" 15

9.5 x 80  
8" x 32" 24



DECOR MIX

20 x 20  
8" x 8" 79



DECOR

20 x 20  
8" x 8" 79

● disponibile in 9 soggetti  
9 subject available

### IMBALLI - PACKING

mm	inch		spessore thickness	pezzi/sc pcs/box	mq/sc sqm/box	kg/sc kgs/box	sc/pl box/pal	mq/pl sqm/pal	kq/pl kgs/pal
80x80	32"x32"	rettificato	10	2	1.28	28.70	40	51.20	1130.80
60x60	24"x24"	rettificato	10	3	1.08	23.90	40	43.20	956.00
30x60	12"x24"	rettificato	10	6	1.08	23.90	40	43.20	956.00
30x30	12"x12"	mosaico		11	0.99	19.70	36	35.64	709.20
30x34	12"x13"	hexagon		6		12.78			
20x20	8"x8"	decor mix		24	0.96	20.78	72	69.12	1496.16
20x20	8"x8"	decor		24	0.96	*	72	69.12	*
7x60	3"x24"	battiscopa smaltato rettificato		12		12.60			
9.5x80	4"x32"	battiscopa smaltato rettificato		8		15.12			

\*

decor W/R 01-02-03-04-05: kg/sc 20.82 - kg/pl 1499.04

decor CL 01-03: kg/sc 20.55 - kg/pl 1479.60

decor CL 02-04: kg/sc 20.84 - kg/pl 1500.48

decor CL 05: kg/sc 20.82 - kg/pl 1499.04

il peso riportato è comprensivo del pallet di supporto - the indicated weight includes the supporting pallet - le poids indiqué est compris de la palette de support - das angegebene gewicht versteht sich einschließlich der palette

### FUGHE - JOINT - JOINT - FUGE

per materiale rettificato prevedere una fuga di almeno 2 mm sul monoformato e necessariamente 3 mm sul multifformato  
por rectified material, we recommend a 2 mm grout at least when using one size only and a 3 mm grout for multisizes laying solution  
pour le matériel rectifié prévoir un minimum de 2mm de joint et 3mm pour la pose multifformat  
fuer retifiziertes material-monoverlegung wollen sie bitte eine fugue von 2 mm vorsehen - fuer modolverlegung eine fugue von 3 mm